



RevNo	Revision Notes	Date	Checked
1	RoHS Compliant	052005	GC



RECOMMENDED
STRIP LENGTHS
.086" 75 OHM



RoHS Compliant

MATERIAL

BODY	BRASS
BODY PLATING	GOLD
CONTACT	BERYLLIUM COPPER
CONTACT PLATING	GOLD
DIELECTRIC	TEFLON (PTFE)

75 Ohm IMPEDANCE
500V PEAK VOLTAGE RATING
TEMPERATURE RANGE: -55°C TO +155°C
INTERFACE DIMENSIONS SIMILAR TO MIL-C-39012

MILLIMETER WAVE TECHNOLOGIES
6501 W. FRYE ROAD, #23
CHANDLER, AZ 85226

SMB FEMALE RIGHT ANGLE
CRIMP CABLE END
for .086" 75 Ohm

Designed by N. JAIN	Checked by W. CANON	Approved by A. LEE	File name MWB-6018-g-08675	TITLE MWB-6018-G-08675
------------------------	------------------------	-----------------------	-------------------------------	---------------------------

TOLERANCES UNLESS OTHERWISE SPECIFIED
DIMENSIONS IN DECIMALS: .XX, .X, .02, .01, .005
DIMENSIONS IN FRACTIONS: XX/64, XX/32, XX/16, XX/8, XX/4, XX/2
DO NOT SCALE THIS DRAWING

ALL DIMENSIONS ON THIS DRAWING ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE.

REV.	Scale
1	NONE
DATE	Sheet
052005	1 of 1