


RevNo	Revision Notes	Date	Checked
1	Initial Release	10/22/20	PC
2	Shell rollover revised to increase pull force	09/20/21	PC



RoHS Compliant

MATERIALS

BODY	BRASS
BODY PLATING	GOLD
CONTACT	BERYLLIUM COPPER
CONTACT PLATING	GOLD
DIELECTRIC	TEFLON (PTFE)
FERRULE	BRASS
FERRULE PLATING	GOLD

50 Ohm IMPEDANCE
 500V PEAK VOLTAGE RATING
 TEMPERATURE RANGE: -55°C TO +155°C
 INTERFACE DIMENSIONS SIMILAR TO MIL-C-39012

MILLIMETER WAVE TECHNOLOGIES
 6501 W. FRYE ROAD, #23
 CHANDLER, AZ 85226

SMC PLUG CRIMP CABLE END
 for RG316

Designed by N. JAIN	Checked by W. CANON	Approved by A. LEE	File name MWC-6001-A-G-316	TITLE MWC-6001-A-G-316
<p>ALL DIMENSIONS ON THIS DRAWING ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE.</p>				
<p>TOLERANCES DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED DECIMALS ± .02 .XXX ± .005</p>		REV. 2	DATE 10/22/20	Scale NONE Sheet 1 of 1