

RoHS Compliant

MATERIAL	RIAL
BODY	BRASS/BeCu
BODY PLATING	GOLD
CONTACT	BeCu
CONTACT PLATING	GOLD
DIELECTRIC (X2)	TEFLON (PTFE)
CAP	BRASS
CAP PLATING	GOLD

MATERIAL	RIAL
BODY	BRASS/BeCu
BODY PLATING	GOLD
CONTACT	BeCu
CONTACT PLATING	GOLD
DIELECTRIC (X2)	TEFLON (PTFE)
CAP	BRASS
CAP PLATING	GOLD
50 Ohm IMPEDANCE	

MILLIMETER WAVE TECHNOLOGIES

SMP FEMALE RIGHT

SOLDER CABLE for RG178

END ANGLE

6501 W. FRYE ROAD, #23 CHANDLER, AZ 85226

	Designed by	Checked by	Approved by	File name TITI F		
		((((((((((((((((((((ייל די ייין נין			1
OU ONM IMPEDANCE	Z. JAIZ	W. CANON	A. LEE	MWP-8001-G-178 W W T - O	0001-6-	- 0
500V PEAK VOLTAGE RATING	TOLEF	RANCES			REV.	Scale
TEMPERATURE RANGE: -55°C TO +155°C	DIMENSIONS ARE IN INCHESS OTHERWISE SPECIFIED OFFINALS ONCH AND	SPECIFIED ANGLEAD	ALL DIMENSIONS	ALL DIMENSIONS ON THIS DRAWING ARE FOR REFERENCE		NONE
INTERFACE DIMENSIONS SIMILAR TO MIL-C-39012	.XX ± .02	+ 300	PURPOSES (PURPOSES ONLY AND ARE SUBJECT TO CHANGE.	DATE	Sheet
	DO NOT SCALE	THIS DRAWING			022015	1 of 1

DATE 022015

Sheet 1 of 1